





P.C.B. LAYOUT

N =Number of contacts

SIGN	DATE	DESCRIPTION	APPROVER
△			
△			
△			

材质于电镀/Material

塑件/Insulator body:

PA66, UL94V-0

焊针/Pin header:

Brass ,Tin planted

电器性能/Electrical

参考标准/Standard:

UL

IEC

额定电压/Rated voltage:

300V

320V

额定电流/Rated current:

12A

15A

接触电阻/Contact resistance:

20m Ω (max)

绝缘电阻/Insulation resistance:

500M Ω /500V

耐电压/Withstanding voltage:

AC 2000V/1Min

机械性能/Mechanical

温度范围/Temperature range:

-40°C to +105°C

瞬间温度/Max soldering:

+250°C, for 5 Sec

尺寸/Dimensions

间距/Pitch:

5.0mm

极数/Poles:

2-4P

慈溪万海电子有限公司
CIXI WANHAI ELECTRONICS CO., LTD.

PART. NAME: 2EDGLF-5.00-XXP

TITLE:

PART. NO.:

DWG NAME:

APPROVED BY

CHECKED BY

DESIGNED BY

DRAWN BY

CUSTOM NO.:



UNITS: mm

SCALE: 4/1

REVISIONB2

Tolerance

x. ± 0.50

x.x ± 0.30

x.xx ± 0.10

xx° $\pm 1^\circ$