

1

2

3

4





5

6

7

△			
△			
△			

P.C.B. LAYOUT



$N = \text{Number of contacts}$

材质于电镀/Material

塑件/Insulator body:

PA66, UL94V-0

焊针/Pin header:

Brass, Tin planted

电器性能/Electrical

参考标准/Standard:

UL

IEC

额定电压/Rated voltage:

300V

450V

额定电流/Rated current:

15A

20A

接触电阻/Contact resistance:

20mΩ (max)

绝缘电阻/Insulation resistance:

500MΩ /500V

耐电压/Withstanding voltage:

AC 2000V/1Min

机械性能/Mechanical

温度范围/Temperature range:

-40°C to +105°C

瞬间温度/Max soldering:

+250°C, for 5 Sec

尺寸/Dimensions

间距/Pitch:

7.62mm

极数/Poles:

2-24P

慈溪万海电子有限公司
CIXI WANHAI ELECTRONICS CO., LTD.

PART. NAME: 2EDGVC-7.62-XXP

TITLE:

PART. NO.:

DWG NAME:

APPROVED BY

CHECKED BY

DESIGNED BY

DRAWN BY

CUSTOM NO.:

Tolerance

x. ±0.50

x.x ±0.30

x.xx ±0.10

xx° ±1°



UNITS: mm

SCALE: 4/1

REVISION B2